

352x High Speed PTZ Camera

ST-C1009/SPAN Series



Features:

- Miniature 5-inch Profile & Integrated Construction
- OSD (On-screen Display)
- 352x Total Zoom, 22x Optical & 16x Digital
- Built-in Multi Protocol such as Pelco, Vicon, Sensormatic, Philips, Kalatel...
- Built-in Memory to store Presets, Tours, Pattern Auto Scan
- Optional Day & Night (SPDN100/SPDN200)

Camera Features

Scan System	2:1 Interlacing
Image Sensor	1/3" Sony CCD
Resolution	480 Lines
Zoom Ratio	352x (Opt. 22x, Digi. 16x)
Sync System	Internal
Video Output	1.0±0.2Vp-p
S/N	more than 50dB
Sensitivity	0.7 lux
White Balance	Auto/Manual
BLC	Off/Auto

Optical Lens

Aperture (F)	F1.6~F3.7
Focal Length	f=3.9~85.8mm

Mechanical

Pan/Tilt Speed	0.5° ~ 160°/s
Preset Speed	> 300°/s
Rotation	Pan 360° continuously Tilt 0° - 90°

Zoom Speed	5 seconds
Auto Flip	3.9s / 6.3s (wide/tele)

Operation Features

Preset	80
Auto Pan	0° ~ 355° Programmable
Display Area	8 with Titles
Pattern	4

Environmental

Environmental Temp.	-40°F~158°F (Outdoor) -0°F~122°F (Indoor)
Environmental Humi.	0~95%
Protection Grade	IP68 Weather Proof TVS 1500W thunder Proof

Electrical

Power Supply	AC24V 50/60Hz
Power Consumption	50W (Outdoor) 10W (Indoor)

General

Receiver	Built-in
Video Output	Female BNC/UTP
Remote Control	RS485/422, Manchester Code, BI-phase, Coaxitron
ID Range	1~254